



Deka's rugged Outdoorsman line provides maintenance-free performance.

- Plenty of cranking amps to power tractors and recreational vehicles across the roughest terrain. Outdoorsman batteries have the power to perform in winter's bitter cold and summer's scorching heat.
- The flush cover Group U1 is calcium **maintenance-free**, eliminating the need to add water and delivering more power-per-pound and **longer storage life** season after season.
- The **flush cover** eliminates the danger of harmful acid spills and lost vent caps, providing **safer and easier operation**. Flush cover batteries replace original equipment batteries more easily because there are no pod vents to interfere with hold-downs and cables.
- Flush cover batteries are **completely leakproof and spillproof** when tipped to a 45° angle, so you don't have to worry about electrolyte leakage when performing routine maintenance.
- **Envelope separators** protect all sides of the plates, preventing internal shorting and providing **superior cranking capacity**.
- Tough **lightweight polypropylene cases** resist breakage under the roughest conditions.
- More than **250 quality control checks** guarantee the highest quality, and all Deka batteries are **made in the U.S.A.**



QUALITY SYSTEM
CERTIFIED TO
ISO 9001
ISO/TS 16949
ISO 14001



"POWERED FOR PERFORMANCE"®

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4781

Order Department Hotline: 610-682-4231

www.dekabatteries.com • e-mail: eastpenn@eastpenn-deka.com

DISTRIBUTED BY:

LAWN & GARDEN / SMALL ENGINE



LAWN & GARDEN / SMALL ENGINE

GRP. NO.	PART NO.		FOOTNOTES	PERFORMANCE LEVEL				QUARTS (LITERS) OF ACID	APPROXIMATE WEIGHT lbs (kgs.)		MAXIMUM OVERALL DIMENSIONS inches (mm)			
	WET	DRY		CCA @ 0°F	RESERVE CAPACITY	A.H. @ 10 HRS.	REF. CA @ 32°F		WET	DRY	L	W	H	
12-VOLT LAWN MOWER — GARDEN TRACTOR — SMALL ENGINE CALCIUM MAINTENANCE-FREE														
U1	11U1L	—	22,Z	350	—	—	410	—	19 (8.6)	—	11.5 (5.2)	7¼ (197)	5½ (130)	7¼ (184)
	10U1L	—	22,Z	300	—	—	365	—	17 (7.7)	—				
	9U1L	9U1LD	8,22,30,Z	275	—	—	335	2½ (2.4)	16.5 (7.5)	—				
	8U1L	—	22,Z	230	—	—	275	—	15.5 (7.0)	—				
	7U1L	—	22,Z	195	—	—	235	—	15 (6.8)	—				
5U1L	—	22,Z	165	—	—	190	—	15 (6.8)	—					
U1R	10U1R	—	22,Y	300	—	—	365	—	17 (7.7)	—	11.5 (5.2)	7¼ (197)	5½ (130)	7¼ (184)
	9U1R	9U1RD	8,22,30,Y	275	—	—	335	2½ (2.4)	16.5 (7.5)	—				
	8U1R	—	22,Y	230	—	—	275	—	15.5 (7.0)	—				
	7U1R	—	22,Y	195	—	—	235	—	15 (6.8)	—				
	5U1R	—	22,Y	165	—	—	190	—	15 (6.8)	—				
22F	522FMF	522FMFD	30	425	65	—	540	4½ (4.3)	29.5 (13.4)	18 (8.2)	9% (238)	6¼ (171)	8¼ (210)	
22NF	322NF	322NFD	12,30	360	58	—	430	4 (3.8)	29 (13.2)	17.5 (7.9)	9% (238)	5½ (140)	9 (229)	
<i>U1 = left front positive; U1R = right front positive (with terminal side of battery facing you)</i>														
OTHER 12-VOLT BATTERIES USED IN LAWN & GARDEN/SMALL ENGINE APPLICATIONS														
26	526MF	—	17,18,22,37	540	80	—	665	—	29.5 (13.4)	—	8% (222)	6% (171)	8 (203)	
	426MF	—	17,18,22,37	450	60	—	560	—	26 (11.79)	—				
26R	526RMF	—	17,18,22,37	540	80	—	665	—	29.5 (13.4)	—	8% (222)	6% (171)	8 (203)	
	426RMF	—	17,18,22,37	450	60	—	560	—	26 (11.79)	—				
	12N103A2	—	—	—	—	10	—	—	—	5.8 (2.6)	5½ (135)	3¾ (90)	5¼ (146)	
	12N12A-4A-1	—	30	—	—	12	—	—	—	6.8 (3.1)	5½ (135)	3¾ (81)	6¾ (160)	
	12N14-3A	—	30	—	—	14	—	—	—	7.5 (3.4)	5½ (135)	3½ (89)	6¾ (167)	
	12N16-3B	—	30	—	—	16	—	—	—	11.8 (5.4)	6% (175)	4 (102)	6% (156)	
	12N9-3A	—	30	—	—	9	—	—	—	5.4 (2.4)	5½ (135)	3 (76)	5½ (140)	
	12N9-4B-1	—	30	—	—	9	—	—	—	5.4 (2.4)	5½ (135)	3 (76)	5½ (140)	
	40B19L(S)	—	30	—	275	52	—	—	2½ (2.5)	—	16.5 (7.5)	7% (197)	5½ (129)	8½ (227)
46B24R	—	30	—	330	75	—	—	3½ (3.3)	—	19.8 (9)	9% (206)	5½ (129)	8½ (227)	
	46B24L(S)	—	30	330	75	—	—	3½ (3.3)	—	19.8 (9)				
NS60	—	—	—	—	75	—	330	—	—	19.8 (9)	9% (206)	5½ (129)	8½ (227)	
	NS60L	—	—	—	75	—	330	—	—	19.8 (9)				
Y50-N18L-A	—	30	—	—	—	20	—	—	—	11.2 (5.1)	8% (206)	3¾ (91)	6% (162)	
	Y50-N18L-A3	—	30	—	—	20	—	—	—	11.2 (5.1)				
YB9-B	—	30	—	—	—	9	—	—	—	5.3 (2.4)	5½ (135)	3 (76)	5¼ (140)	
	YB10L-A2	—	30	—	—	11	—	—	—	7.0 (3.2)	5½ (135)	3¾ (90)	5¼ (146)	
	YB12A-A	—	30	—	—	12	—	—	—	6.8 (3.1)	5½ (135)	3¾ (81)	6¾ (160)	
	YB14L-A2	—	30	—	—	14	—	—	—	7.6 (3.4)	5½ (135)	3½ (89)	6¾ (167)	
	YB16-B	—	30	—	—	19	—	—	—	10.5 (4.8)	6% (175)	4 (102)	6% (156)	
	YB16-B-LM	—	30	—	—	19	—	—	—	10.5 (4.8)	6% (175)	4 (102)	6% (156)	
	YB16CLB	—	30	—	—	19	—	—	—	10.1 (4.5)	6% (175)	4 (102)	6% (175)	
	YB16L-B	—	30	—	—	19	—	—	—	10.5 (4.8)	6% (175)	4 (102)	6% (156)	
OTHER 12-VOLT AGM BATTERIES USED IN LAWN & GARDEN/SMALL ENGINE APPLICATIONS														
ETX15	—	—	2,38,39,42,76	210	—	14	—	—	11 (5.0)	—	5¼ (134)	3½ (89)	6¾ (167)	
	ETX15L	—	2,38,39	210	—	14	—	—	11 (5.0)	—	5¼ (134)	3½ (89)	6¾ (167)	
	ETX16	—	2,38,39,42,74,77	275	—	19	—	—	17 (7.7)	—	6% (175)	4 (102)	6¼ (156)	
	ETX18L	—	2,38,39,77	330	—	20	—	—	18 (8.2)	—	8% (206)	3¾ (91)	6% (163)	
	ETX30L	—	2,38,39,77	365	—	26	—	—	21.7 (9.8)	—	6% (168)	5½ (131)	6% (175)	
YT4L-BS	—	30	—	50	—	3	—	—	—	2.9 (1.3)	4½ (114)	2½ (71)	3% (86)	
YTX14AHBS	—	30	—	210	—	12	—	—	9 (4.1)	—	5½ (135)	3¾ (89)	6¾ (167)	
	YTX14AHLBS	—	30	210	—	12	—	—	9 (4.1)	—	5½ (135)	3¾ (89)	6¾ (167)	
	YTX20BS	—	30	270	—	18	—	—	—	11.2 (5.1)	6% (164)	3¾ (88)	6% (156)	
	YIX30L	—	97	385	—	30	—	—	22 (10)	—	6% (167)	5 (127)	6% (175)	

All batteries have maintenance-free calcium grids except where noted.

All batteries except Powersports have SAE automotive posts unless noted.

All batteries manufactured in polypropylene cases and covers except where noted. Maintenance-free batteries have microporous, polyethylene envelope separators

FOOTNOTES:

- 2 - Black cover / Gray case
- 8 - Dry charged batteries have black covers & white cases
- 11 - Low maintenance – low antimony grids
- 12 - Hybrid construction
- 14 - Centerline terminal posts
- 17 - Includes handle
- 18 - Includes top adapter
- 19 - Includes lifting edges
- 21 - Anchor lock elements
- 20 - Hard rubber, multi-cell cover construction
- 22 - Flush manifold vented cover

- 23 - Flush manifold vented cover when shipped wet, standard cover when shipped dry or FP
- 30 - Available dry-add "D" suffix to part number
- 37 - For height with adapter add 7/8" (22 mm)
- 42 - For height with adapter add 7/8" (22 mm)
- 97 - AGM, activated, ready to install
- S - SAE "automotive type" post
- Y - Small L terminal with round holes
- Z - Small L terminal with square holes

